
FIG. 10J J-HANGER





Material: Carbon Steel, SS304, SS316

Finish: Electro-galv, Stainless Steel 304, Stainless steel 316

**Approvals:** Complies with Manufactures' Standardization Society (MSS) SP-58 & SP-69 (Type 5)

**Ordering:** Specify figure number and finish

**Notes:** Stainless steel hangers are recommended for applications where

protection from a corrosive environment is required.

## **ELECTRO-GALVANIZED**

	Pipe Size	Pipe OD	Bolt	А	В	С	D	E	F	Wgt Each (lbs)	Max Rex Load(lbs)	
N	1/2	0.840	1/4	3/8-16	2-5/8	1-3/4	7/16	1-1/2	1-15/16	0.15	400	
	3/4	1.050	1/4	3/8-16	2-7/8	1-7/8	7/16	1-3/4	2-1/8	0.20	400	
HR	1	1.315	1/4	3/8-16	2-15/16	1-15/16	7/16	1-7/8	2-5/16	0.20	400	DU
	1-1/4	1.660	1/4	3/8-16	3-1/4	2	7/16	2-3/16	2-5/8	0.20	400	
	1-1/2	1.900	1/4	3/8-16	3-9/16	2-13/16	7/16	2-1/2	2-7/8	0.25	400	
N	2	2.375	1/4	3/8-16	3-11/16	2-1/8	7/16	2-11/16	3-1/16	0.25	400	
	2-1/2	2.875	3/8	1/2-13	4-7/16	2-7/16	9/16	2-7/8	3-5/8	0.60	500	
H	3	3.500	3/8	1/2-13	4-13/16	2-9/16	9/16	3-1/2	4-1/16	0.78	500	DU
	3-1/2	4.000	3/8	1/2-13	5-1/8	2-5/8	9/16	3-3/4	4-3/8	1.00	500	
	4	4.500	3/8	5/8-11	6-7/8	3-3/16	9/16	4-1/4	5-3/16	1.10	550	
N	5	5.563	3/8	5/8-11	6-3/4	3-1/4	9/16	5-7/16	5-3/4	1.25	550	
u n	6	6.625	3/8	3/4-10	7-3/4	3-9/16	9/16	5-5/8	6-5/8	2.25	600	n II
П	8	8.625	3/8	7/8-9	9-3/16	3-15/16	9/16	6-3/16	8	2.90	760	υU
	10	10.750	3/8	7/8-9	11-3/16	4-13/16	9/16	7-13/16	10-3/16	3.45	760	

Projec	Approval Stamp		
Project:			Notes:
Address:	Contractor:		
Date:	Engineer:		
Approved Approve	as Noted 🔲	Not Approved	

P: (631) 665-9300 • F: (631) 491-0897 • WWW.ITPNY.NET

FIG. 10J J-HANGER



## STAINLESS 304 AND 316

Pipe Size	Pipe OD	Bolt	Α	В	С	D	Е	F	Wgt Each (lbs)	Max Rex Load(lbs)
1/2	0.840	1/4	3/8-16	2-5/8	1-3/4	7/16	1-1/2	1-15/16	0.21	400
3/4	1.050	1/4	3/8-16	2-7/8	1-7/8	7/16	1-11/16	2-1/8	0.22	400
1	1.315	1/4	3/8-16	2-15/16	1-15/16	7/16	1-7/8	2-5/16	0.25	400
1-1/4	1.660	1/4	3/8-16	3-1/4	2	7/16	1-13/16	2-5/8	0.27	400
1-1/2	1.900	1/4	3/8-16	3-9/16	2-13/16	7/16	2-1/16	2-7/8	0.29	400
2	2.375	1/4	3/8-16	3-11/16	2-1/8	7/16	2-9/16	3-1/16	0.31	400
2-1/2	2.875	3/8	1/2-13	4-7/16	2-7/16	9/16	3-3/16	3-5/8	0.71	500
3	3.500	3/8	1/2-13	4-13/16	2-9/16	9/16	3-1/2	4-1/16	0.78	500
3-1/2	4.000	3/8	1/2-13	5-1/8	2-5/8	9/16	3-3/4	4-3/8	0.84	500
4	4.500	3/8	5/8-11	6-7/8	3-3/16	9/16	4-5/8	5-3/16	1.39	550
5	5.563	3/8	5/8-11	6-3/4	3-1/4	9/16	5-1/16	5-3/4	1.66	550
6	6.625	3/8	3/4-10	7-3/4	3-9/16	9/16	5-13/16	6-5/8	2.26	600
8	8.625	3/8	7/8-9	9-3/16	3-15/16	9/16	6-15/16	8	3.32	760

	Project In	Approval Stamp		
Project:				Notes:
Address:		Contractor:		
Date:		Engineer:		
Approved	Approved as	Noted 🗌	Not Approved	