



**FIG. 26DF
REGULAR EYEBOLT**



Material: Drop Forged, Furnished with standard hex nuts
Finish: Plain, galvanized, or stainless steel.
Ordering: Specify size, figure number and finish.
Notes: See Warnings for proper use

GALVANIZED

Shank Diameter and Length	Length of Thread	Eye Inside Dimension	Eye Outside Dimension	Weight Each	Working Load Limit
1/4 x 2	1.5	0.50	1.00	0.07	500
1/4 x 4	2.5	0.50	1.00	0.12	500
5/16 x 2-1/4	1.5	0.62	1.25	0.13	800
5/16 x 4-1/4	2.5	0.62	1.25	0.20	800
3/8 x 2-1/2	1.5	0.75	1.50	0.24	1,200
3/8 x 4-1/2	2.5	0.75	1.50	0.31	1,200
3/8 x 6	2.5	0.75	1.50	0.35	1,200
1/2 x 3-1/4	1.5	1.00	2.00	0.55	2,200
1/2 x 6	3	1.00	2.00	0.74	2,200
1/2 x 8	3	1.00	2.00	0.78	2,200
1/2 x 10	3	1.00	2.00	0.88	2,200
1/2 x 12	3	1.00	2.00	1.05	2,200
5/8 x 4	2	1.25	2.50	1.01	3,500
5/8 x 6	3	1.25	2.50	1.15	3,500
5/8 x 8	3	1.25	2.50	1.31	3,500
5/8 x 10	3	1.25	2.50	1.52	3,500
5/8 x 12	4	1.25	2.50	1.86	3,500
5/8 x 15	5	1.25	2.50	2.00	3,500
5/8 x 18	5	1.25	2.50	2.10	3,500
5/8 x 21	5.5	1.25	2.50	2.40	3,500
5/8 x 24	5.5	1.25	2.50	2.65	3,500
3/4 x 4-1/2	2	1.50	3.00	1.56	5,200
3/4 x 6	3	1.50	3.00	1.84	5,200
3/4 x 8	3	1.50	3.00	2.08	5,200
3/4 x 10	3	1.50	3.00	2.30	5,200
3/4 x 12	4	1.50	3.00	2.52	5,200
3/4 x 15	5	1.50	3.00	3.10	5,200
7/8 x 5	2.5	1.75	3.50	2.84	7,200
7/8 x 8	4	1.75	3.50	3.20	7,200
7/8 x 12	4	1.75	3.50	3.87	7,200
1 x 6	3	2.00	4.00	3.85	10,000
1 x 9	4	2.00	4.00	4.52	10,000
1 x 12	4	2.00	4.00	5.26	10,000
1 x 18	7	2.00	4.00	6.67	10,000
1-1/4 x 8	4	2.50	5.00	7.50	15,200
1-1/4 x 12	4	2.50	5.00	9.00	15,200
1-1/4 x 20	6	2.50	5.00	12.09	15,200



FIG. 26DF - Regular Eyebolt
 (continued from previous page)

STAINLESS STEEL

Shank Diameter and Length	Length of Thread	Eye Inside Dimension	Eye Outside Dimension	Weight Each	Working Load Limit
1/4 x 2	1.5	0.50	1.00	0.09	500
1/4 x 4	2.5	0.50	1.00	0.12	500
5/16 x 2-1/4	1.5	0.62	1.25	0.16	800
5/16 x 4-1/4	2.5	0.62	1.25	0.17	800
3/8 x 2-1/2	1.5	0.75	1.50	0.24	1,200
3/8 x 4-1/2	2.5	0.75	1.50	0.30	1,200
1/2 x 3-1/4	1.5	1.00	2.00	0.54	2,200
1/2 x 6	3	1.00	2.00	0.69	2,200
5/8 x 4	2	1.25	2.50	1.04	3,500
5/8 x 6	3	1.25	2.50	1.15	3,500
3/4 x 4-1/2	2	1.50	3.00	1.65	5,200
3/4 x 6	3	1.50	3.00	1.38	5,200

Warnings:

- Failure to follow the instructions for use below and these Warnings may cause death or serious injury.
- Rated capacity is drastically reduced when loading at any angle.
- Follow all Warnings, Use and Application Instructions as supplied by the Manufacturer.
- Loading must never be made at an angle greater than 45° from bolt centerline.
- At any angle of 45°, rated capacity is reduced to 1/4 of the tabulated value.
- Loads should always be applied to lifting eyes in the plane of the eye, not at some angle to this plane.
- Shoulder lifting eyes must be properly seated (should bear firmly against the mating part) otherwise the working loads must be reduced substantially. A steel washer or spacer may be required for proper seating.