




**FIG. 26DFS
SHOULDER EYEBOLT**



Material: Drop Forged, Furnished with standard hex nuts
Finish: Plain, galvanized, or stainless steel.
Ordering: Specify size, figure number and finish.
Notes: See Warnings for proper use

GALVANIZED

Shank Diameter and Length	Length of Thread	Eye Inside Dimension	Eye Outside Dimension	Weight Each	Working Load Limit
1/4 x 2	1.5	0.50	0.87	0.07	500
1/4 x 4	2.5	0.50	0.87	0.10	500
5/16 x 2-1/4	1.5	0.62	1.12	0.12	800
5/16 x 4-1/4	2.5	0.62	1.12	0.17	800
3/8 x 2-1/2	1.5	0.75	1.37	0.21	1,200
3/8 x 4-1/2	2.5	0.75	1.37	0.28	1,200
1/2 x 3-1/4	1.5	1.00	1.75	0.42	2,200
1/2 x 6	3	1.00	1.75	0.59	2,200
5/8 x 4	2	1.25	2.25	0.83	3,500
5/8 x 6	3	1.25	2.25	1.00	3,500
3/4 x 4-1/2	2	1.50	2.75	1.54	5,200
3/4 x 6	3	1.50	2.75	1.77	5,200
7/8 x 5	2.5	1.75	3.25	2.23	7,200
7/8 x 8	4	1.75	3.25	2.66	7,200
1 x 6	3	2.00	3.75	3.56	10,000
1 x 9	4	2.00	3.75	4.20	10,000
1-1/2 x 15	6	2.50	5.50	14.25	15,200

STAINLESS STEEL

Shank Diameter and Length	Length of Thread	Eye Inside Dimension	Eye Outside Dimension	Weight Each	Working Load Limit
1/4 x 2	1.5	0.50	0.87	0.09	460
1/4 x 4	2.5	0.50	0.87	0.12	460
5/16 x 2-1/4	1.5	0.62	1.12	0.16	780
5/16 x 4-1/4	2.5	0.62	1.12	0.17	780
3/8 x 2-1/2	1.5	0.75	1.37	0.24	1,160
3/8 x 4-1/2	2.5	0.75	1.37	0.30	1,160
1/2 x 3-1/4	1.5	1.00	1.75	0.54	2,150
1/2 x 6	3	1.00	1.75	0.69	2,150
5/8 x 4	2	1.25	2.25	1.04	3,440
5/8 x 6	3	1.25	2.25	1.25	3,440
3/4 x 4-1/2	2	1.50	2.75	1.65	5,140
3/4 x 6	3	1.50	2.75	1.80	5,140

Warnings:

- Failure to follow the instructions for use below and these Warnings may cause death or serious injury.
- Rated capacity is drastically reduced when loading at any angle.
- Follow all Warnings, Use and Application Instructions as supplied by the Manufacturer.
- Loading must never be made at an angle greater than 45° from bolt centerline.
- At any angle of 45°, rated capacity is reduced to 1/4 of the tabulated value.
- Loads should always be applied to lifting eyes in the plane of the eye, not at some angle to this plane.
- Shoulder lifting eyes must be properly seated (should bear firmly against the mating part) otherwise the working loads must be reduced substantially. A steel washer or spacer may be required for proper seating.