
FIG. 310G "EM-LOK" ADJUSTABLE SWIVEL RING HANGER, DOMESTIC











Material: Pre-galvanized carbon steel.

Finish: Pre-galvanized and plastic coated.

Service: Designed for the suspension of non-insulated stationary pipe

lines. Plastic coating prevents pipe from coming in contact with hanger and is designed to reduce noise, vibration and prevent

electrolysis between pipe and hanger.

Approvals: U.L. - U.L.C. listed and FM approved. Complies with Federal

Specification WW-H-171-E (Type# 10), A-A-1192A (Type# 10) and Manufacturers' Standardization Society MSS SP-58 and SP-69

(Type# 10).

Ordering: Specify pipe size, figure number and finish.

PIPE SIZE	PIPE OD	MATERIAL SIZE	Α	В	С	E	F	G	WGT EACH (lbs)	MAX REC LOAD (lbs)
1/2	0.840	18ga x ⁵ /8	3/8	2 1/2	2 7/8	1 ⁵ /8	13/16	7/8	0.08	400
3/4	1.050	18ga x ⁵ /8	3/8	2 7/16	2 15/16	1 ⁹ /16	11/16	7/8	0.08	400
1	1.315	18ga x ⁵ /8	3/8	2 5/8	3 ¹ / ₄	1 ³ / ₄	11/16	7/8	0.08	600
1 ¹ / ₄	1.660	18ga x 5/8	3/8	2 9/16	3 3/8	1 11/16	7/8	7/8	0.10	600
1 ¹ / ₂	1.900	18ga x ⁵ /8	3/8	2 11/16	3 5/8	1 13/16	7/8	7/8	0.10	600
2	2.375	18ga x ⁵ /8	3/8	3 3/8	4 1/2	2 1/2	¹⁵ / ₁₆	7/8	0.12	600
2 1/2	2.875	14ga x ³/4	1/2	3 11/16	5 ¹ /8	2 3/4	1 ¹ / ₄	11/16	0.32	600
3	3.500	14ga x ³ / ₄	1/2	4	5 ⁷ /8	3 1/8	1 ¹ /8	11/16	0.35	600
3 ¹ / ₂	4.000	14ga x ³ / ₄	1/2	4 ⁵ /16	6 ⁵ /8	3 5/8	1 1/2	11/16	0.39	600
4	4.500	13ga x ³ / ₄	5/8	4 ¹⁵ / ₁₆	7 1/8	3 7/8	1 ¹ /4	1 ¹ /8	0.43	1000
5	5.563	12ga x 1	5/8	5 ⁵ /8	8 ¹ / ₂	4 ³ /8	1 ³ /8	1 ¹ /8	0.65	1000
6	6.625	12ga x 1	3/4	6 11/16	10 ¹ /8	5 5/16	2	1 ³ /8	1.09	1250
8	8.625	11ga x 1	3/4	8 5/16	12 ⁷ /8	6 15/16	2 5/8	13/8	1.24	1250

IMPHOTOLA	Project Information	Approval Stamp
Project:	L /// ///	Notes:
Address:	Contractor:	UCTS / THREADED PRODUCTS
Date:	Engineer:	
Approved	Approved as Noted Not Approve	d 🗆 📉