




**FIG. 320  
(DOMESTIC) & 320I TURNBUCKLE**



**Material/Finish:** Forged steel  304 stainless steel  316 stainless steel   
 Plain  electro-galvanized  hot-dip galvanized

**Service:** Hanger rod connector, tapped right hand x left hand thread to provide up to 6 inches of adjustment. Normally tapped for UNC-2A thread (standard).

**Approvals:** Complies with Federal Specification WW-H-171-E (Type# 13), A-A-1192A (Type# 13) and Manufacturers' Standardization Society MSS SP-58 and SP-69 (Type# 13).

**Ordering:** Specify size, figure number and finish.

**Notes:** When figure 320I is supplied hot-dip galvanized, it is not tapped oversize.



Manufactured in the USA  
Excluding 320I

| SIZE A  | WGT EACH (lbs) | MAX REC LOAD (lbs) |       |
|---------|----------------|--------------------|-------|
|         |                | 650°F              | 700°F |
| 3/8-16  | 0.42           | 610                | 540   |
| 1/2-13  | 0.65           | 1130               | 1010  |
| 5/8-11  | 0.98           | 1810               | 1610  |
| 3/4-10  | 1.50           | 2710               | 2420  |
| 7/8-11  | 1.90           | 3770               | 3360  |
| 1-8     | 2.60           | 4960               | 4420  |
| 1 1/8-7 | 4.20           | 6230               | 5560  |
| 1 1/4-7 | 4.50           | 8000               | 7140  |
| 1 1/2-6 | 6.40           | 11630              | 10370 |

| Project Information               |  | Approval Stamp                        |
|-----------------------------------|--|---------------------------------------|
| Project:                          |  | Notes:                                |
| Address:                          | Contractor:                                |                                       |
| Date:                             | Engineer:                                  |                                       |
| Approved <input type="checkbox"/> | Approved as Noted <input type="checkbox"/> | Not Approved <input type="checkbox"/> |