
FIG. 41H SPLIT RING EXTENSION HANGER, HINGE DESIGN





Material: Malleable iron.

Finish: Plain, electro-galvalized.

Designed for suspension of non-insulated stationary pipe lines Service:

horizontally or vertically.

Complies with Federal Specification WWH-171-E. (Type# 25), A-A-1192A (Type# 12), Manufacturers' Standardization Society SP-58 and MSS SP-69 (Type# 12). Approvals:

Specify pipe size, figure number and finish. Ordering:

PIPE SIZE	PIPE OD	SCREW	А	В	С	D	WEIGHT EACH (lbs)	MAX REC LOAD (lbs)
3/8	0.675	10-24	3/8-16	11/16	1 13/16	1 ³ /16	0.084	180
1/2	0.840		3/8-16	3/4	2 1/8	1 ³ /16	0.098	
3/4	1.050		3/8-16	7/8	2 1/2	1 ⁹ /16	0.112	
CUDICIS	1.315		3/8-16	1 ¹ /8	2 ³ / ₄	2	0.147	
1 ¹ / ₄	1.660		3/8-16	1 ⁵ /16	3 ³ /16	2 ³ /8	0.181	
1 1/2	1.900		3/8-16	1 ⁷ /16	3 ³ /8	2 5/8	0.214	
2	2.375		3/8-16	1 5/8	3 15/16	3 ¹ / ₁₆	0.299	
2 1/2	2.875	7	1/2-13	2 1/8	5 ³ / ₁₆	3 13/16	0.583	INDUG
3	3.500	1/4	1/2-13	2 1/2	5 11/16	4 ⁵ /8	0.713	300
4	4.500		1/2-13	2 7/8	6 ³ / ₄	5 9/16	1.019	IIIILADED

\			

Project In	Approval Stamp		
Project:	Notes:		
Address:	Contractor:	THREADED PRODUCTS	
Date:	Engineer:		
Approved Approved as I	MINDUCTRIAL		