
## FIG. 802 HEAVY WELDED BRACKET





Material/Finish: Carbon steel ☐ 304 stainless steel ☐ 316 stainless steel Plain 🔲 electro-galvanized hot-dip galvanized painted Recommended for the support of pipe loads up to 3000 lbs Service: Constructed of facing angle iron with 1" space. The bracket provides maximum lateral adjustment when carrying or suspending pipe. Complies with Federal Specification WW-H-171-E (Type# 34), **Approvals:** A-A-1192A (Type# 33) and Manufacturers' Standardization Society MSS SP 58 and SP 69 (Type# 33). Specify size number, figure number and finish. Ordering:



SIZE NO.	C-C	Α	PEO	E	\$ <sub>H</sub>	В	L	ANGLE SIZE S	W	WGT EACH (lbs)
	15 <sup>1</sup> / <sub>4</sub>	12	ONE HOLE	2 <sup>3</sup> / <sub>4</sub>	13/16	1 1/2	18	2 x 1 <sup>1</sup> / <sub>2</sub> x <sup>1</sup> / <sub>4</sub>	4	25.00
2	21 <sup>3</sup> /8	18	2 3/4	2 3/4	<sup>15</sup> / <sub>16</sub>	1 <sup>3</sup> /8	24	2 x 2 x <sup>1</sup> / <sub>4</sub>	5	38.00
3	27 <sup>1</sup> / <sub>2</sub>	24	2 1/2	2 3/4	1 1/16	1 1/4	30	2 <sup>1</sup> / <sub>2</sub> x 2 x <sup>5</sup> / <sub>16</sub>	5	69.00
4	33 <sup>1</sup> / <sub>4</sub>	30	2 1/2	3	1 1/16	1 1/2	36	2 <sup>1</sup> / <sub>2</sub> x 2 x <sup>5</sup> / <sub>16</sub>	5	82.10
5	39	36	3 <sup>1</sup> / <sub>2</sub>	3	1 <sup>1</sup> /16	1 1/2	42	3 <sup>1</sup> / <sub>2</sub> x 2 <sup>1</sup> / <sub>2</sub> x <sup>3</sup> / <sub>8</sub>	6	130.00
6	46	42	3 1/2	3 1/2	1 <sup>1</sup> /16	2	50	3 <sup>1</sup> / <sub>2</sub> x 2 <sup>1</sup> / <sub>2</sub> x <sup>3</sup> / <sub>8</sub>	6	155.00

Project	Approval Stamp		
Project:	INDUSTRIAL)	Notes:	
Address:	Contractor:	THREADED PRODUCTS	
Date:	Engineer:		
Approved Approved a	INDUCTORAL		