


8250

OD Tubing Strut Clamp Assembled

Material: Electro-galvanized carbon steel.
Also available in 304 stainless steel.



Pipe Size	Max Rec Load (lbs)	Weight Each (lbs)	Pipe Size	Max Rec Load (lbs)	Weight Each (lbs)
1/4"	400	0.09	3-3/4"	1000	0.51
3/8"		0.09	3-7/8"		0.52
1/2"		0.07	4"		0.52
5/8"		0.09	4-1/8"		0.53
3/4"		0.13	4-1/4"		0.54
7/8"		0.14	4-3/8"		0.55
1"	600	0.15	4-1/2"	1000	0.55
1-1/8"		0.16	4-5/8"		0.57
1-1/4"		0.18	4-3/4"		0.58
1-3/8"		0.19	4-7/8"		0.60
1-1/2"		0.20	5"		0.62
1-5/8"		0.21	5-1/8"		0.64
1-3/4"		0.22	5-1/4"		0.66
1-7/8"		0.22	5-3/8"		0.68
2"		0.23	5-1/2"		0.70
2-1/8"		0.23	5-5/8"		0.72
2-1/4"		0.25	5-3/4"		0.74
2-3/8"		0.26	5-7/8"		0.76
2-1/2"	800	0.38	6"	1000	0.79
2-5/8"		0.38	6-1/8"		0.83
2-3/4"		0.39	6-1/4"		0.87
2-7/8"		0.40	6-3/8"		0.90
3"		0.42	6-1/2"		0.95
3-1/8"		0.44	6-5/8"		1.02
3-1/4"		0.46	6-3/4"		1.05
3-3/8"		0.48	6-7/8"		1.10
3-1/2"		0.50	7"		1.16
3-5/8"		0.50	8-3/8"		1.25

USE THE FOLLOWING CLAMPS FOR NO-HUB CAST IRON SOIL PIPE

No-Hub Cast Iron Nominal Pipe Size	Use The Following Strut Clamp
1-1/2"	8200 - 1-1/2"
2"	8200 - 2"
3"	8250 - 3-3/8"
4"	8250 - 4-3/8"
5"	8250 - 5-3/8"
6"	8250 - 6-3/8"
8"	8250 - 8-3/8"
10"-12"	CALL