


**FIG. 907**  
**4-Way Sway Brace Attachment**



**Material:** Steel, hardened cone (or cup) point set screw.

**Finish:** Plain.

**Service:** For bracing pipe against sway and seismic disturbances; functions as a longitude brace connection when attached to a lateral brace pipe. Bracing connection must be positioned as close as physically possible to the braced pipe.

**Approvals:** Approved by the State of California Office of Statewide Health Planning and Development (OSHPD).

**Ordering:** Figure number, bracing pipe sizes, and finish.

Can be attached on either side of the pipe being braced.

Part Number	Brace Pipe Size		A		B		Maximum Design Load lbs (kN)	Approximate Wgt/100 lbs (kg)
	in	mm	in	mm	in	mm		
907 -1 x 1	1 x 1	25 x 25	4-3/4	120.6	4-3/4	120.6	655* (2.91)	103 (46.7)
907 - 1 x 1-1/4	1 x 1-1/4	25 x 32	5-3/16	128.6	4-13/16	122.2	655* (2.91)	107 (48.5)
1-1/4 x 1-1/4	1-1/4 x 1-1/4	32 x 32	5-3/8	136.5	5-1/4	133.1	655* (2.91)	109 (49.4)

\* Load will accommodate up to 4" (100mm) pipe at maximum spacing.

Project Information		Approval Stamp
Project:		Notes:
Address:	Contractor:	
Date:	Engineer:	
Approved <input type="checkbox"/> Approved as Noted <input type="checkbox"/> Not Approved <input type="checkbox"/>		