




**BASE WITH 14 GA. (1.9MM)
GALV. CHANNEL – 1" (25.4MM) HIGH**



Dimensions: 5" (127mm) High x 6" (152mm) Wide x Length (overall length)

Ordering: Specify figure number and model number.

Ultimate Load Capacity:

(uniform load) For roof loading, consult roof manufacturer or engineer. As with most commercial roofs, the weakest point may be the insulation board beneath the rubber membrane.

UPC/Part #	Model #	Height in (mm)	Width in (mm)	Overall Length	Weight Each	Ultimate Load Capacity
782051/50035	DB 5	5 (127)	6 (152)	4.8 (122)	2.75 (1.25kg)	200 lbs (0.89kN)
782051/49972	DB 10	5 (127)	6 (152)	9.6 (244)	5.28 (2.39kg)	500 lbs (2.22kN)
782051/49974	DB 20	5 (127)	6 (152)	20.2 (5123)	10.63 (4.82kg)	1000 lbs (4.45kN)
782051/50021	DB 30	5 (127)	6 (152)	30.8 (782)	15.99 (7.25kg)	1500 lbs (6.67kN)
782051/50022	DB 40	5 (127)	6 (152)	41.4 (1052)	21.34 (9.68kg)	2000 lbs (8.89kN)
782051/50023	DB 48	5 (127)	6 (152)	52.0 (1321)	26.70 (12.4kg)	2500 lbs (11.12kN)